

## SBT-00021 Storage of SolarBridge Products

# Purpose

---

This document provides information to individuals responsible for the safe storage of the following SolarBridge products:

- SolarBridge Pantheon™ Microinverter
- SolarBridge Power Manager
- SolarBridge AC cables and accessories

# Requirements

---

The SolarBridge products are designed to withstand extreme external environments for long periods of time. Consequently, they are tolerant of a wide range of storage temperatures and humidity. SolarBridge products do not expire while in storage. Packaging and accompanying documents could be susceptible to discoloration / deformation if exposed to wet environments or excessive UV.

In a storage facility that meets recommended conditions for a professional warehouse, including protection from fire, theft, vermin, and insects, the SolarBridge products can be stored indefinitely under the following environmental conditions:

- Temperature range
- Microinverter – -40C to +65C
- Power Manager – -20C to +65C
- Accessories – -40C to +65C
- Humidity range of 10 to 95% RH (non-condensing)
- Protected from excessive dust, hazardous chemicals or gases
- Protected from excessive UV exposure
- Protected from falling water (rain, condensation from air conditioning, broken water pipes, flooding, etc.)

However, the products and their performance are subject to the terms and conditions of the applicable limited product warranty provided by SolarBridge, and such warranty has a finite life.

If you have any questions about either short- or long-term storage, please contact SolarBridge Technologies for assistance.